

DESCRIPTION


- ELECTRONIC BALLAST
- ELECTRONIC TRANSFORMER
- SWITCH MODE POWER SUPPLY

FEATURES:

- LOW THERMAL RESISTANCE
- HIGH INPUT RESISTANCE
- FAST SWITCHING
- ROHS COMPLIANT

MAXIMUM RATINGS (Tc=25°C)

PARAMETER	SYMBOL	VALUE	UNIT
Drain-source Voltage	VDS	700	V
gate-source Voltage	VGS	±30	V
Continuous Drain Current (TC=25°C)	ID	5	A
Drain Current-Pulsed	IDM	12	A
Total Dissipation	PD	26	W
Junction Temperature	Tj	150	°C
Storage Temperature	Tstg	-55-150	°C
Single Pulse Avalanche Energy (IAS=5A)	EAS	46	mJ

MECHANICAL

ELECTRONIC CHARACTERISTICS (Tc=25°C)

CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	MAX	UNIT
Drain-source Breakdown Voltage	BVDSS	VGS=0V, ID=250 μ A	700		V
Gate Threshold Voltage	VGS (TH)	VGS=VDS , ID=250 μ A	2.5	4.5	V
Drain-source Leakage Current	IDSS	VDS=700V, VGS=0V		1	uA
Drain-Source Diode Forward Voltage	VSD	VGS=0V, IS=5A		1.5	V
Gate-body Leakage Current (VDS = 0)	IGSS	VGS=±30V		±100	nA
Static Drain-source On Resistance	RDS (ON)	VGS=10V, ID=2.5A		1100	mΩ
Thermal Resistance Junction-case	RthJ-c			4.8	°C/W

■ DYNAMIC CHARACTERISTICS (T_c=25°C)

CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V, f=1.0MHZ	-	320	-	pF
output Capacitance	C _{oss}		-	75	-	pF
Reverse Transfer Capacitance	C _{rss}		-	5	-	pF

■ SWITCHING CHARACTERISTICS (T_c=25°C)


CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Turn-On Delay Time	t _{d(on)}	V _{DD} =400V, I _D =2.5A, R _G =20Ω, V _{GS} =10V	-	10	-	ns
Turn-On Rise Time	t _r		-	8	-	ns
Turn-Off Delay Time	t _{d(off)}		-	60	-	ns
Turn-Off Rise Time	t _f		-	13	-	ns
Total Gate Charge	Q _g	V _{DS} =480V, I _D =2.5A, V _{GS} =10V	-	15	-	nC
Gate-Source Charge	Q _{gs}		-	3	-	nC
Gate-Drain Charge	Q _{gd}		-	6	-	nC

■ DRAIN-SOURCE DIODE MAXIMUM RATINGS AND CHARACTERISTICS (T_c=25°C)


CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Max. Diode Forward Current	I _s		-	-	5	A
Max. Pulsed Forward Current	I _{SM}		-	-	12	A
Diode Forward Voltage	V _{SD}	V _{GS} =0V, I _S =5A	-	-	1.5	V
Reverse Recovery Time	t _{rr}	V _{GS} =0V, I _S =2.5A, dI _F /dt=100A/μs,	-	180	-	ns
Reverse Recovery Charge	Q _{rr}		-	1.5	-	μC




CHARACTERISTICS CURVE




Output Characteristic




Transfer Characteristic




On Resistance Vs Drain Current



Safe Operating Area




On Resistance Vs Junction Temperature




Capacitance




CHARACTERISTICS CURVE



Gate Charge Waveform



Source-Drain Diode Forward Voltage



Breakdown Voltage Vs Junction Temperature



TO-220F MECHANICAL DATA

UNIT: mm

SYMBOL	MIN	NOM	MAX	SYMBOL	MIN	NOM	MAX
A	4.5		4.9	E1	6.5	7	7.5
A1	2.3		2.9	e	2.44	2.54	2.64
b	0.65		0.9	L	12.5		14.3
b1	1.1		1.7	L1	9.45		10.05
b2	1.2		1.4	L2	15		16
c	0.35		0.65	L3	3.2		4.4
D	14.5		16.5	ΦP	3		3.3
D1	6.1		6.9	Q	2.5		2.9
E	9.6		10.3				

